



INSTALL IT. ENJOY QUIETNESS.

# ArmaComfort Barrier P

High performance flexible fire and  
acoustic pearly white mass loaded sound  
barrier

- // Excellent at reducing the transmission of airborne sound with low thickness
- // Very good fire performance
- // IMO Part 5
- // Environmentally friendly: 100% recyclable
- // Halogen-free, lead-free, bitumen-free and phosphate-free
- // Self-adhesive
- // Easy to install



 **armacell**<sup>®</sup>  
ArmaComfort<sup>™</sup>

## TECHNICAL DATA - ARMACOMFORT BARRIER P

Brief description	High performance mass loaded sound barrier for a quieter environment.
Material type	EVA/EPM
Product colour range	White
Special features	Does not contain lead, bitumen, halogen and phosphate.
Applications	Flexible sheet to reduce airborne sound transmission.
Installation	The substrate must be dry and free of dust and grease. Certified and compatible adhesive for a long-term performing system is ArmaFlex 520.

Property	Value / Assessment	Standard / Test method
<b>Temperature range</b>		
Service temperature <sup>1</sup>	Min. °C	EN 14304
	-20	
<b>Fire Performance and Approvals</b>		
Reaction to fire	B-s1,d0 B-s2,d0 (self-adhesive)	EN 13501-1, EN 13823, EN ISO 11925-2
<b>UL standards</b>		
UL 94 V-0	⌀ 2.5 mm	IEC 60695-11-10
<b>Fire performance</b>		
Others	Pass	IMO 2010 FTP Code, Part 5
<b>Physical attributes</b>		
Density	≥ 2050 kg/m <sup>3</sup>	
Dimensions and tolerances	In accordance with EN 14314 table 1.	EN 822, EN 823, EN 13467
<b>Mechanical properties</b>		
Tensile strength	>1 N/mm <sup>2</sup>	ASTM D412 (Die A)
Elongation at break	20 %	ASTM D412 (Die A)
Hardness (Shore A)	85 ± 10	
<b>Acoustic performance</b>		
Weighted sound reduction index, Rw [C ; Ctr] [dB]	1mm: 23 dB [C;Ctr] = [-1;-4] dB 2mm: 27 dB [C;Ctr] = [-1;-3] dB 3mm: 30 dB [C;Ctr] = [-1;-4] dB 4mm: 32 dB [C;Ctr] = [-1;-3] dB 5mm: 34 dB [C;Ctr] = [-1;-3] dB	ISO 10140-1
<b>Other technical features</b>		
Application conditions	Application temperature between 5°C and 30°C with relative humidity <80%.	
Shelf life <sup>2</sup>	Self-adhesive sheets: 1 year	
Storage	Can be stored in dry and clean rooms at normal relative humidity (50% to 70%) and ambient temperature (0°C to 35°C).	

<sup>1</sup>For use in temperatures beyond the published value, please contact Technical Services.

<sup>2</sup>Shelf life (maximum storage time) is limited to ensure that only currently manufactured products are installed on projects. This limitation is restricted solely to storage of the product and does not affect the lifetime of product after it has been installed.

All data and technical information are based on results achieved under the specific conditions defined according to the testing standards referenced. Despite taking every precaution to ensure that said data and technical information are up to date, Armacell does not make any representation or warranty, express or implied, as to the accuracy, content or completeness of said data and technical information. Armacell also does not assume any liability towards any person resulting from the use of said data or technical information. Armacell reserves the right to revoke, modify or amend this document at any moment. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer. This document does not constitute nor is part of a legal offer to sell or to contract.

At Armacell, your trust means everything to us, so we want to let you know your rights and make it easier for you to understand what information we collect and why we collect it. If you would like to find out about our processing of your data, please visit our Data Protection Policy.

Trademarks followed by © or ™ are trademarks of the Armacell Group. © Armacell, 2024. All rights reserved.

TDS | 032024 | en-GB

## ABOUT ARMACELL

---

As the inventor of flexible foam for equipment insulation and a leading provider of engineered foams, Armacell develops innovative and safe thermal and mechanical solutions that create sustainable value for its customers. Armacell's products significantly contribute to global energy efficiency making a difference around the world every day. With more than 3,300 employees and 25 production plants in 19 countries, the company operates two main businesses, Advanced Insulation and Engineered Foams. Armacell focuses on insulation materials for technical equipment, high-performance foams for acoustic and lightweight applications, recycled PET products, next-generation aerogel technology and passive fire protection systems.

For more information, please visit:  
[www.armacell.com](http://www.armacell.com)

